

PR9+



SPECIALISED PRINTER

PR9+ is the specialised printer for multifunctional front-office applications capable to print on **single-sheet and multiple-copy documents and on passbooks**.

PR9+ handles a full range of bank teller forms, recognizes passbook magnetic stripes, reads CMC7 and E13B codes and provides **simultaneous dual-side scanning** for documents with widths of up to 210 mm(optional).

Equipped with a full character-generator set, **PR9+** is an efficient device to meet local compliance requirements around the world.

Stylish and ergonomic, with an optimized design, **PR9+** keeps dimensions to a minimum, ranking as one of the **smallest specialised printers** for this market segment.



MAIN CHARACTERISTICS

- ONE OF THE SMALLEST AND QUIETEST IN ITS PRODUCT CLASS
- EXTREMELY EASY TO USE
- MANAGEMENT OF ALL BANK FORMS
- ULTRA-FAST ALIGNMENT FOR IMPROVED PERFORMANCE
- DUAL-SIDE COLOUR SCANNING (OPTIONAL)
- MAGNETIC-STRIP READING-WRITING, MICR CODELINE READING
- OUTSTANDING GRAPHICS MANAGEMENT
- SUPERIOR PRINTING SPEEDS: UP TO 660 CHAR/SEC IN VHSD
- NEW INK RIBBON PRINTS UP TO 10 MILLION CHARACTERS

DESCRIPTION

All models feature an innovative CPU and the new 2295 Hz printhead for outstanding productivity on texts and graphics alike. The printer produces 291 pages per hour on the ECMA Test, more than any other model in its product class.

Attention to printing quality is combined with superior productivity: PR9+ uses a new-generation ink ribbon able to print up to 10 million characters. The 24-pin printhead (0.25 mm diameter) is designed to service the entire machine life (at least 5 years) and manage a daily workload of more than 300 transactions at competitive speeds.

The standard model provides RS 232, IEEE 1284 parallel and USB 2.0 interfaces. Options include: second USB port, second serial port and Ethernet interface.

TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS

Technology	24-pin dot matrix
Resolution	240 x 360 dpi
Fonts	OCR A-B, ROMAN, Sans Serif, Italic, Courier
Pitch	10, 12, 15, 16.6, 17.1, 20 cpi
Printing speed at 10 cpi	VHSD: 660 cps - HSD: 520 cps Draft: 400 cps - NLQ: 200 cps LQ: 135 cps - BIM: 2000 dps
Line length	238,76 mm (94 columns at 10 cpi)
Line spacing	1/5", 1/6", n/216", n/240"
Copies	Original + 6 copies
Interfaces	Standard: RS232 serial, IEEE 1284 parallel and USB 2.0 Optional: second USB port, second serial port and Ethernet interface
Emulations	Olivetti Standard, IBM PP & X24 Optional: IBM 4722/9068, IBM PP & X24, WINCOR 4915, EPSON LQ 2550, UNISYS EFP series
Noise level	< 52 dBA
Document Handling	<ul style="list-style-type: none"> • Feed width: 245 mm • Max thickness: 4 mm • Completely flat paper feed • Automatic insertion with autoborder • Automatic document-thickness monitoring
Power consumption	Min. 25 W - Max. 85 W (printing)
Ribbon cartridge	10 million characters
Voltage	230V / 50Hz - 115V / 60Hz
Certifications & Regulatory	CE, TÜV NRTL, FCC class A verified
Dimensions (WxDxH)	384 x 296 x 204 mm (15.12" x 11.65" x 8.03")
Weight	10.5 Kg
Input Buffer	32-256KB
Options	MICR reader (CMC7, E13B) Double Color printing (red & black)

* Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners.



PT MURNI SOLUSINDO NUSANTARA
Digital Business Transformation Center

Branch Transformation | Digital Marketing | Managed Services | Public Information Display
Customer Experience Solutions | Maintenance Services | Cash & Cheque Processing Solutions



30+ YEARS
OF EXPERIENCES



TRUSTED BY
MAJOR COMPANIES
ACROSS SECTORS



NATIONWIDE
TECHNICAL SUPPORT
WITH 75+ SERVICE POINTS
AND 24/7 HELPDESK



CORE COMPETENCY IN
BANKING & OFFICE
EQUIPMENTS



SUPPORTED BY MORE THAN
500 DEDICATED STAFF
AND TECHNICIANS

JAKARTA (Head Office & Multisector Simulation Room)

Jl. Lingkar Luar Barat No.1, Jakarta Barat 11750, Indonesia
 +62-21 584 1060
 +62-21 587 4505

BANDUNG +62-22 205 63705

SURABAYA +62-31 593 0010

MEDAN +62-61 453 2994

YOGYAKARTA +62-274 883 506

DENPASAR +62-361 499 323

SEMARANG +62-24 764 34391



PT Murni Solusindo Nusantara 1500 913 (Sales) 1500 013 (Helpdesk) info@murni.co.id

ISO 9001:2015 Certified No. ID 14/02656

WWW.MURNI.CO.ID

©PT Murni Solusindo Nusantara. All products, images and brand names are trademarks and owned by respective company and are used for descriptive purpose only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purpose without prior notice.